



CITY OF MT. VERNON INVITATION TO BID

SEALED BIDS FOR PUBLIC UTILITIES ROLL-OFF TRUCK

Bids will be accepted by the City Clerk's office at City Hall, 1100 Main St. Mt. Vernon, IL. 62864. October 7th, 2026, until 1:00 p.m. October 28th, 2026. Bids will be opened at this time. Bid forms/specifications may be obtained from the City Clerk's office. All bids must be sealed and labeled: **PU ROLL-OFF TRUCK**

Bids will be awarded at the November 2nd, 2026, Council Meeting. For further information contact Mike Shannon, Fleet Services Director at 618-242-6855.



SPECIFICATIONS

Each bid shall be accompanied by a set of "Specifications" consisting of a detailed description of the equipment.

PURCHASER'S OBLIGATIONS

The purchaser reserves the right to accept or reject any or all bids on such a basis as the purchaser deems to be in its best interest. All bidders should be advised that the purchaser is not bound in any manner to automatically accept the lowest bid. The City Council reserves the right to reject any and/or all bids and to accept which is most advantageous to the City of Mt. Vernon.

ACQUAINTANCE WITH SPECIFICATIONS

It is the responsibility of the bidder to review all the bidding requirements. The failure of a bidder to be acquainted with this information shall not relieve them of any obligations of the bid requirements.

BID FORMS / SPECIFICATIONS

All bid forms shall be submitted on the attached bid form. The bid form and / or these specifications shall be filled out by checking either the "YES" or "NO" column for each section / paragraph. Failure to use this form and / or these specifications shall be cause for immediate rejection of any bid.

EXCEPTION TO SPECIFICATIONS

The following specifications shall be strictly adhered to. Exceptions shall be allowed if they are equal to or superior to that specified (as judged by the purchaser), and provided they are listed and fully explained on a separate page entitled "EXCEPTIONS TO SPECIFICATIONS". Each check in the "NO" column shall be listed and fully explained. If a section contains an empty column, where the bidder neglected to check the proper "YES" or "NO" column, it is assumed the bidder is not conforming to the requirements of this bid. If no explanation is given in the "EXCEPTIONS TO SPECIFICATIONS" document the bid is subject to immediate rejection.

DELIVERY AND SETUP

Delivery and setup to the City of Mount Vernon will be included in the bid price.
Delivery date must be submitted on bid sheet.



SPECIAL NOTE

Due to recent issues with surcharges and upcharges, bidders should anticipate fluctuations in prices. The awarded bid shall be strictly adhered to; all pricing shall be final. Any extra charges or price fluctuations shall be the responsibility of the bidder and not of the purchaser. Any charges incurred after the award of the bid will only be paid by the purchaser if modifications or additions are made by the purchaser after the bid has been awarded.

BID SUMMERIZATION:

1 – Tandem truck with roll-off cable hoist for 18-22ft containers



SPECIFICATIONS

DESCRIPTION	YES	NO
--------------------	------------	-----------

Truck Chassis Specifications

Minimum Front Axle Capacity: 18,000Lb.		
Minimum Rear Axle Capacity: 44,000Lb.		
Tandem Walking Beam Suspension or similar.		
Truck Frame: 100,000 PSI or more Chassis Frame		
Required Truck CT: 174" from the first unobstructed point behind the cab to the center of the tandem axles		
Maximum Distance for the standard length configuration from ground level to top of frame: 43"		
Maximum Outside Tire Spread of Tandem: 96"		
Minimum Required After Frame: 25" back from the center of the rear most axle.		

Truck Engine

Engine configuration: inline 6 cyl.		
Fuel type: Diesel		
Minimum Horsepower: 450hp.		

Truck Transmission

Allison RDS 3500 or heavier		
-----------------------------	--	--

Hoist Specifications

Manufacturers rated capacity: 60,000Lb.		
Manufacturers factory tested lifting and pull-on capacity: 60,000Lb.		
Recommended container Lengths: 18-22 Ft		
Working hydraulic pressure: 1850 PSI		
Raised dump angle: 48 degrees		
Main frame: (2) 8" x 4" x 1/2" A500 Grade "C" rectangular tubing main rails.		



Hoist Specifications	YES	NO
Sub frame: (2) 3" x 2" x 205" x 3/16" A500 grade "C" rectangular tubing rails		
Front container stops: 1 1/2" HR plate steel		
Front container safety lock: 1" A36 Plate steel latch that is pushed up by a tempered spring when the hoist is completely lowered.		
Air operated roll-off container locking system that automatically engages and disengages to secure the roll-off container to the hoist.		
Winch rail: Constructed of 4" structural channel . 3/8" Steel plate formed crossmember.		
Side roller assembly: Five per side (4" O.D. x 2" I.D.) outside rail.		
Cable sheave: Sheaves are a 10" ductile iron casting		
Cable sheave shafts: 2 1/2" diameter		
Cable sheave guides: 4" structural channel		
Winch cylinder rod guards: 1/4" x 6" A36 plate V formed.		
ICC Bumper: Fabricated to hinge. Can be folded up to bottom of hoist frame and pinned in place to allow for towing trailers		
ICC Bumper includes pneumatic actuator to automatically fold up bumper		
Bumper automatically folds up completely when the hoist is raised		
Cable: 7/8" diameter x 71' long, 6 x 37 XIP IWRC regular right lay, core color coded; - Manufacturers rated capacity minimum of 39 tons. Line pull on cable at 1850 PSI: 35,594Lb.		
Cable pick up end: cast steel swivel cable eye - Tested to 78,000Lb, and secured by cold flowing swaged fittings.		
Cable anchor: (4) 7/8" Forged Cable Clamps, Hot Galvanized		
Pump: gear type, 42 GPM @ 1500 RPM		
Inside air controls allowing control of hoist from drivers seat.		
Outside manual control Levers allowing control of hoist cylinders.		
Lifetime warranty on hoist frame		
Minimum 2 year warranty on hydraulic cylinders		



EXCEPTIONS TO SPECIFICATIONS PAGE



Creativity Redefined!

Bid Sheet

Company Name: _____

Submitted By: _____

Date of Bid: _____

Bid Price: _____

Delivery Date of truck: _____